

SR27



Automation Grade SEMI Fully Use Intensity Low MEDIUM High Format Setting Manual AUTOMATIC Box Dimension Small MEDIUM LARGE

DATASHEET

Semi-Automatic Case Sealer


The **SR27** is a new semi-automatic case sealing machine designed and engineered by SIAT specifically for large random sized boxes. SR27 is the ideal case sealing machine for a variety of industries like E-commerce, Logistics, Electronics and Tissue.


KEY FEATURES


- ✓ Practical Seals upper & lower flaps of cardboard cases or cartons
- ✓ Added Protection Lockable electric isolation switch
- ✓ Taping Heads Available with K11 or K12 taping heads
- ✓ Faster 30 m/min belt conveyor speed option available
- ✓ Ecological energy saving option available

- ✓ Quality Build Best-In-Class components with SIEMENS electrics and FESTO pneumatic components
- ✓ New feature Top taping head removable
- ✓ Improved Design Quick release Taping Heads (Top & Bottom - No tools required)
- ✓ CE compliant Engineered and produced in Italy according to EU safety standards

MACHINE DIMENSIONS







Compres Sup	
Max. 6	6 bar
NL/Cycle	9

Machine Dimensions		
Min (mm) Max (mn		Max (mm)
H Column	1.465	1.805
H Bench	485	825
w	910	910
W Bench	720	720
L	1.400	1.400

Standard Po	ower Supply
380/400V -	50Hz - 3ph
440V - 6	OHz - 3ph
Amps	1,08
Power kW	0,26
Phase	3Ph +N + PE




DATASHEET

Technical Data	
Belt position	Top + Bottom
Box Size	Medium + Large
Min / Max box weight	0.5 - 32 kg
Default Taping Head	K12 for 3" = 75 mm
Alternative Taping Heads	K11 for 2" = 50 mm
Power Consumption (std.)	0,26 kw
Air Consumption (NL/Cycle)	9
Operator Side	Left (std.) / Right
Tape width (mm)	75 (std.) / 50
Tape Leg (mm)	70 (std.) / 50 / 30
Ingress Protection Code	IP54
Ambient Operating Temperature	+5° / +40° C
Maximum level of noise	Depending on tape quality
Features	
Removable Top Taping-Head	
Removable Bottom Taping-Head	•
Adjustable Tape Leg	•
Pre-Installed & Easy-To-Mount	<u> </u>
Adjustable Tape Contact Pressure	•
Autom. Box Format Setting	•
Flap Folding Function	•
Belt Speed Selection	-
Fully Automatic Operation	-
SIAT Taping-Logic on board	-

MORE MACHINE DIMENSIONS

Length x Width	1.400 x 910
Workbench Width	720
Height H (std. legs)	1.465 - 1.805
Height H1 (std. legs + wheels AS77)	1.575 – 1.915
Height H2 (opt. legs AS80)	1.625 – 1.960
Height H3 (opt. legs AS80 + wheels AS77) Workbench	1.735 – 2.070
Height Z (std. legs)	485 – 825
Workbench Height Z1 (std. legs + wheels AS77)	595 – 935
Workbench Height Z2 (opt. legs AS80)	645 – 980
Workbench Height Z3 (opt. legs AS80 + wheels AS77)	755 – 1.090



SPECIAL VERSIONS

Special Versions according to individual application and safety requirements are possible on request.









BOX DIMENSIONS & PRODUCTIVITY



Box Dimensions	L (mm)	W (mm)	H (mm)
Min.	150	170	100*
Max.	∞	650	670

* 100 mm high box manageable with 50 mm tape leg 120 mm high box manageable with 70 mm tape leg




Max. production capacity: Up to 650* BPH

*Based on the shortest processible box length and provided an optimum continous box infeed by the operator

PROCESSABLE TAPES

Base Material	PVC / OPP / PET / Paper*
Adhesive Type	Solvent / Hot Melt / Acrylic
Special Tape	Filament-Tape** / Safety-Seal-Tape***

*with limitations **special tape cutting blade required ***need of a test might be necessary



	K11R / K12R
Α	Max. 410 mm
В	50 / 75 mm
С	76 mm

BOX REQUIREMENTS

Quality result of the taped box depends on the general box quality and dimensional accuracy, as well as the quality of tape used.

Box Types: FEFCO 0201 - RSC [other types may be possible as well]

	Underfilling
Adverse	
Impact	
Factors	A





OPTIONS & ACCESSORIES

- Operation side "Right" (std. "Left")
- Special cutting blades filament-tape
- Taping Head for 50mm width
- Power Supply 220/230V 50hz 1ph
- Higher Legs
- Casters / Wheels
- Fix / Extendable Roller Conveyors
- Safety fences
- 30 m/min belt speed (std. 22)
- Energy Saving Kit
- End/Break Tape Device

MORE DETAILS

Videos and further information can be found on our website or SIAT Youtube channel.







